

CONDITIONAL-ACCESS MODULE (CAM)



CAM is Conditional Access Module with common conditional access interface (Common Interface) in TVs and digital television receivers. The CAM allows to provide subscribers with access to encrypted content in digital television.

The CAM is Conditional Access Module of the DVCrypt scrambling system with common conditional access interface (Common Interface) in TVs and digital television receivers. CAM allows to provide subscribers with access to encrypted content in digital television.

The CAM supports DVCrypt video content scrambling system.

CAM is made in the PCMCIA form factor.

The CAM is equipped with slot for installation of smart cards (Subscriber CAS cards).

Physical characteristics	
Dimensions	 PCMCIA Type II; 100 x 58 x 5 mm (Length x Width x Depth)
Connector	68-pin PCMCIA
Interface protocols	
CI-interface protocols	according to profile 1 DVB-CI protocol and PCMCIA specifications
Protocols of the smart card interface	built-in smartcard reader;ISO7816 standard
Electrical characteristics	
Operating voltage	3 ~ 5V

Taking into consideration that we (UMT LLC) are developer and system integrator, also do not stop on our technical growth and improvement, know that view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters listed on each device webpage.

Note! All details customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each our customer has 1.5 year warranty and 7 year aftersales support for whole range of our products.